



EDC6 (1889) DTZS  
IEC 62783-1:2019

## DRAFT TANZANIA STANDARD

(Draft for comments only)

---

**Twinax cables for digital communications - Part 1: Generic specification**

**TANZANIA BUREAU OF STANDARDS**

---

## 1 National Foreword

This draft Tanzania Standard is being prepared by the Telecommunications and Information Technology Technical Committee, under the supervision of the Electrotechnical divisional standards committee (EDC)

This draft Tanzania Standard is an adoption of the International Standard **IEC 62783-1:2019** Twinax cables for digital communications - Part 1: Generic specification, Which has been prepared by the International Electrotechnical Commission

## 2 Terminology and conventions

Some terminologies and certain conventions are not identical with those used in Tanzania standards; attention is drawn especially to the following: -

- 1) The comma has been used as a decimal marker for metric dimensions. In Tanzania Standards, it is current practice to use “full point” on the baseline as the decimal marker.
- 2) Where the words “International Standard(s)” appear, referring to this standard they should read “Tanzania Standard(s)”.

Draft for Stakeholders' comments only

# INTERNATIONAL STANDARD

---

**Twinax cables for digital communications**  
**– Part 1: Generic specification**

INTERNATIONAL  
ELECTROTECHNICAL  
COMMISSION

---

ICS 33.120.20

ISBN 978-2-8322-6249-8

**Warning! Make sure that you obtained this publication from an authorized distributor.**

## CONTENTS

FOREWORD .....	4
INTRODUCTION.....	6
1 Scope .....	7
2 Normative references .....	7
3 Terms and definitions .....	9
4 Requirements for cables construction .....	9
4.1 General remarks .....	9
4.2 Cable construction .....	9
4.2.1 General .....	9
4.2.2 Conductor .....	9
4.2.3 Insulation .....	10
4.2.4 Colour code .....	10
4.2.5 Drain wire .....	10
4.2.6 Screening of cable assembly element .....	10
4.2.7 Cable make-up .....	10
4.2.8 Screening of the cable core .....	10
4.2.9 Sheath .....	10
4.2.10 Colour of sheath .....	11
4.2.11 Identification .....	11
4.2.12 Finished cable .....	11
5 Requirements and test methods .....	11
5.1 General .....	11
5.2 Electrical tests .....	12
5.2.1 Conductor resistance .....	12
5.2.2 Resistance unbalance.....	12
5.2.3 Dielectric strength .....	12
5.2.4 Insulation resistance .....	12
5.2.5 Mutual capacitance .....	12
5.2.6 Surface transfer impedance .....	12
5.3 Transmission requirements and tests .....	12
5.3.1 General .....	12
5.3.2 Characteristic impedance .....	13
5.3.3 Return loss .....	13
5.3.4 Attenuation .....	13
5.3.5 Propagation delay, inter-element delay skew, and intra-element delay skew .....	14
5.3.6 Near-end crosstalk (NEXT) .....	14
5.3.7 Attenuation to crosstalk ratio far-end (ACR-F) .....	15
5.3.8 Transverse conversion loss (TCL) .....	15
5.3.9 Equal level transverse conversion transfer loss (ELTCTL) .....	15
5.3.10 Screening attenuation .....	15
5.3.11 Coupling attenuation .....	15
5.4 Mechanical and dimensional requirements and test methods .....	15
5.4.1 General .....	15
5.4.2 Measurement of dimensions .....	15
5.4.3 Elongation at break of the conductor.....	16
5.4.4 Tensile strength of the insulation .....	16

5.4.5	Elongation at break of the sheath .....	16
5.4.6	Tensile strength of the sheath .....	16
5.4.7	Crush test of the cable .....	16
5.4.8	Impact test of the cable .....	16
5.4.9	Repeated bending of the cable .....	16
5.4.10	Tensile performance of the cable .....	16
5.5	Environmental tests .....	16
5.5.1	Shrinkage of the insulation .....	16
5.5.2	Wrapping test of the insulation after thermal ageing .....	16
5.5.3	Bending test of the insulation at low temperature .....	16
5.5.4	Tensile strength and elongation of the sheath after ageing .....	16
5.5.5	Sheath pressure test at high temperature .....	16
5.5.6	Cold bend test of the cable .....	17
5.5.7	Heat shock test .....	17
5.5.8	Flame propagation characteristics of a single cable .....	17
5.5.9	Flame propagation characteristics of bunched cables .....	17
5.5.10	Smoke generation .....	17
5.5.11	Combined flame and smoke test for cables in environmental air handling spaces .....	17
Bibliography	.....	18
Table 1 – Nominal attenuation values, dB/10 m .....		13

## INTERNATIONAL ELECTROTECHNICAL COMMISSION

**TWINAX CABLES FOR DIGITAL COMMUNICATIONS – Part 1: Generic****specification FOREWORD**

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as "IEC Publication(s)"). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC itself does not provide any attestation of conformity. Independent certification bodies provide conformity assessment services and, in some areas, access to IEC marks of conformity. IEC is not responsible for any services carried out by independent certification bodies.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard IEC 62783-1 has been prepared by subcommittee 46C: Wires and symmetric cables, of IEC technical committee 46: Cables, wires, waveguides, RF connectors, RF and microwave passive components and accessories.

The text of this International Standard is based on the following documents:

FDIS	Report on voting
46C/1107/FDIS	46C/1113/RVD

Full information on the voting for the approval of this International Standard can be found in the report on voting indicated in the above table.

This document has been drafted in accordance with the ISO/IEC Directives, Part 2.

A list of all parts in the IEC 62783 series, published under the general title *Twinax cables for digital communications*, can be found on the IEC website.

The committee has decided that the contents of this document will remain unchanged until the stability date indicated on the IEC website under "<http://webstore.iec.ch>" in the data related to the specific document. At this date, the document will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

A bilingual version of this publication may be issued at a later date.

Draft for Stakeholders' comments only

## INTRODUCTION

This International Standard specifies the generic characteristics of twinax cables, which use multiple twinax cable elements for transmission of digital signals.

These cables are intended for use in high-performance information technology systems and data interface interconnection systems. Twinax cables are generally used in short-reach data communication links, which reach about 1 m to 10 m. Information technology interconnection standards that use twinax cables include Ethernet, Fibre channel, SAS, SATA, and others.

IEC 62783 (all parts) includes separate family specifications, which are provided for each information technology interconnection standard's specific twinax cable requirements.

Draft for Stakeholders' comments only



# TWINAX CABLES FOR DIGITAL COMMUNICATIONS –

## Part 1: Generic specification

### 1 Scope

This part of IEC 62783 specifies definitions and requirements of twinax cables used in digital communication systems. These cables are intended to be used in indoor applications. This generic specification details the requirements and transmission characteristics for single twinax elements as well as multiple twinax elements within the same sheath, i.e. “twinax cable”.

This generic specification is supplemented with family specifications that give additional requirements based on the specific application, e.g. the maximum specified frequency of the cables.

### 2 Normative references

The following documents are referred to in the text in such a way that some or all of their content constitutes requirements of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60028, *International standard of resistance for copper*

IEC 60068 (all parts), *Environmental testing*

IEC 60189-1, *Low-frequency cables and wires with PVC insulation and PVC sheath – Part 1: General test and measuring methods*

IEC 60304, *Standard colours for insulation for low-frequency cables and wires*

IEC 60332- 1-2, *Tests on electric and optical fibre cables under fire conditions – Part 1-2: Test for vertical flame propagation for a single insulated wire or cable – Procedure for 1 kW pre-mixed flame*

IEC 60332- 2-2, *Tests on electric and optical fibre cables under fire conditions – Part 2-2: Test for vertical flame propagation for a single small insulated wire or cable – Procedure for diffusion flame*

IEC 60332-3-10, *Tests on electric and optical fibre cables under fire conditions – Part 3-10: Test for vertical flame spread of vertically-mounted bunched wires or cables – Apparatus*

IEC TR 60344, *Calculation of d.c. resistance of plain and coated copper conductors of low-frequency cables and wires – Application guide*

IEC 60708, *Low-frequency cables with polyolefin insulation and moisture barrier polyolefin sheath*

IEC 60794- 1- 2, *Optical fibre cables – Part 1-2: Generic specification – Basic optical cable test procedures – General guidance*

- IEC 60811-201, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 201: General tests – Measurement of insulation thickness*
- IEC 60811-203, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 203: General tests – Measurement of overall dimensions*
- IEC 60811-401, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 401: Miscellaneous tests – Thermal ageing methods – Ageing in an air oven*
- IEC 60811-406, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 406: Miscellaneous tests – Resistance to stress cracking of polyethylene and polypropylene compounds*
- IEC 60811-501, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 501: Mechanical tests – Tests for determining the mechanical properties of insulating and sheathing compounds*
- IEC 60811-502, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 502: Mechanical tests – Shrinkage test for insulations*
- IEC 60811-504, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 504: Mechanical tests – Bending tests at low temperature for insulation and sheaths*
- IEC 60811-506, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 506: Mechanical tests – Impact test at low temperature for insulations and sheaths*
- IEC 60811-508, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 508: Mechanical tests – Pressure test at high temperature for insulation and sheaths*
- IEC 60811-509, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 509: Mechanical tests – Test for resistance of insulations and sheaths to cracking (heat shock test)*
- IEC 60811-510, *Electric and optical fibre cables – Test methods for non-metallic materials – Part 510: Mechanical tests – Methods specific to polyethylene and polypropylene compounds – Wrapping test after thermal ageing in air*
- IEC 61034 (all parts), *Measurement of smoke density of electric cables burning under defined conditions*
- IEC 61156-1, *Multicore and symmetrical pair/quad cables for digital communications – Part 1: Generic specification*
- IEC TR 61156-1-2, *Multicore and symmetrical pair/quad cables for digital communications – Part 1-2: Electrical transmission characteristics and test methods of symmetrical pair/quad cables*
- IEC 62153-4 -3, *Metallic communication cable test methods – Part 4-3: Electromagnetic compatibility (EMC) – Surface transfer impedance – Triaxial method*
- IEC 62153-4 (all parts), *Metallic communication cable test methods – Part 4: Electromagnetic compatibility (EMC)*
- IEC 62153-4 -4, *Metallic communication cable test methods – Part 4-4: Electromagnetic compatibility (EMC) – Test method for measuring of the screening attenuation as up to and above 3 GHz, triaxial method*

IEC 62153-4-9, *Metallic communication cable test methods – Part 4-9: Electromagnetic compatibility (EMC) – Coupling attenuation of screened balanced cables, triaxial method*

### 3 Terms and definitions

For the purposes of this document, the following terms and definitions apply.

ISO and IEC maintain terminological databases for use in standardization at the following addresses:

- IEC Electropedia: available at <http://www.electropedia.org/>
- ISO Online browsing platform: available at <http://www.iso.org/obp>

#### 3.1

##### **twinax element**

pair of insulated conductors that are laid parallel, side-by-side, enclosed in a metal foil shield with drain wire (known also as twin-axial or twin-coaxial)

#### 3.2

##### **twinax cable**

cable composed of multiple twinax elements

#### 3.3

##### **twinax cable assembly**

twinax cable terminated on both ends with a connector

### 4 Requirements for cables construction

#### 4.1 General remarks

The nominal twinax characteristic impedance is 100  $\Omega$ . Normal twinax cable configurations range from 2 to 32 elements, with a conductor size range from 0,2 mm to 0,6 mm (original designs used 32 AWG to 22 AWG), or other sizes as specified in the family.

The choice of materials and cable construction shall be suitable for the intended application and installation of the cable. Particular care shall be taken to meet any special requirements for fire performance (such as burning properties, smoke generation, evolution of acid gas, etc.).

#### 4.2 Cable construction

##### 4.2.1 General

The cable construction shall be in accordance with the details and dimensions given in the relevant family specification.

##### 4.2.2 Conductor

The conductor shall consist of annealed copper in accordance with IEC 60028, shall be solid or stranded and circular in cross-section, and shall be silver-coated, tin-coated, bare copper, plated copper or copper alloy.

The conductor DC resistance and resistance unbalance, when specified, shall meet the values indicated in the relevant family specification. The maximum conductor DC resistance shall be calculated in accordance with IEC TR 60344.